


Product Image



Product Dimensions



Characteristics

Nominal Voltage		12V
Nominal Capacity (20 hour rate)		240Ah
Capacity 25°C (77°F)	10 hour rate (21.6A)	216Ah
	5 hour rate (38.2A)	191Ah
	1 hour rate (133.3A)	133.3Ah
Internal Resistance	Full Charged Battery 25°C	≤1.5mΩ
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	0°C (32°F)	85%
	-15°C (5°F)	65%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 48A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 48A Voltage 14.4-14.9V

Packaging

Battery Dimensions	Length	520mm
	Width	269mm
	Height	203mm
	Total Height	209mm
Box Dimensions	Length	537mm
	Width	284mm
	Height	299mm
Quantity Per Box		1 PC per box
Net weight Per Cell		71.0kg±3%
Net weight Per Box		71.0kg
Gross Weight		71.8kg

Discharge Constant Current per Cell (Amperes at 77°F/25°C)







F.V/Time	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h	24h	100h
1.60V	308.9	196.7	145.2	133.3	84.6	59.4	40.4	26.7	23.8	13	12.9	2.88
1.65V	303.3	193.1	142.6	130.9	83.1	58.3	39.7	26.2	23.3	12.7	12.7	2.82
1.70V	297.6	189.5	139.9	128.5	81.5	57.2	38.9	25.7	22.9	12.5	12.5	2.77
1.75V	292.0	186.0	137.3	126.0	80.0	56.2	38.2	25.2	22.5	12.2	12.2	2.72
1.80V	280.8	178.8	132.0	121.2	76.9	54.0	36.7	24.2	21.6	12.0	11.8	2.66

Discharge Constant Power per Cell (Watts at 77°F 25°C)

F.V/Time	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h	24h	100h
1.60V	594.6	378.6	279.5	256.6	162.9	114.3	77.8	51.3	45.7	24.9	24.9	5.54
1.65V	583.8	371.7	274.4	252.0	159.9	112.3	76.3	50.4	44.9	24.5	24.4	5.44
1.70V	573.0	364.8	269.3	247.3	157.0	110.2	74.9	49.5	44.1	24.0	24.0	5.33
1.75V	562.2	358.0	264.3	242.6	154.0	108.1	73.5	48.5	43.2	23.6	23.5	5.23
1.80V	540.5	344.2	254.1	233.3	148.1	104.0	70.7	46.7	41.6	23.1	22.6	5.13

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact **MCA** for the latest information.

Performance Characteristics



Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Copper	Fiberglass	Sulfuric acid